



PRODUCT DATA SHEET

KZN ATF II

AUTOMATIC TRANSMISSION FLUID

Description

ATF II is blended with high quality refined base oils including multifunctional additives plus red dye which is suitable for universal performance and for longer periods. It is formulated using additives containing viscosity index improvers, anti-oxidants, anti wear agents, detergents and special additives to provide controlled frictional characteristics.

Advantages

- Provides controlled frictional characteristics.
- Maximizes transmission life.
- Smooth operation.
- Increase oil life.

Applications

Recommended for power shift transmission fluids and industrial and mobile hydraulic fluids and for use in off- highway equipment. It has excellent lubrication at all operating temperatures.

Quality Levels

ATF DEXRON II meets or exceeds the following performance requirements:

DEXRON®- IID(General Motors)

Ford MERCON®*.

Caterpillar TO-2.

Allison C4

Hagglunds Denison HF-0

Typical Characteristics

| | |
|----------------------------------|------------|
| SAE Viscosity Grade | R-IID |
| Viscosity @40C | 37.0cSt |
| Viscosity @ 100C | 7.10cSt |
| Kinematic Viscosity Index | 158 |
| Density @ 20C | 0.8680kg/l |
| Pour Point | -49 °.C |
| Flash Point | >200 |
| Colour (Visual) | Red |