



PRODUCT DATA SHEET

KZN INDUSTRIAL GEAR OIL 150

CONVENTIONAL INDUSTRIAL GEAR OIL

Description

KZN Gear Oil 150 is blended with solvent refined base oils incorporating Sulphur/ Phosphorous additives which provides excellent protection under extreme pressure conditions. The formulation provides very good corrosion protection ,anti-foam characteristics and oxidation resistance.

Advantages

- Excellent high temperature oxidation stability and cleanliness.
- Impressive water -separating ability
- Excellent rust and corrosion inhibition
- Exceptional load carrying capability.

Application

Recommended for extreme pressure protection, exceptional oxidation stability and superior rust inhibition in the gearbox system and compatible with most leaded gear oils.

Quality Levels

Industrial Gear Oil 150 meets or exceeds the following performance standards.
US STEEL 224 Lead Free EP Gear Oil.
DAVID BROWN SI.53.101
ANSI /AGMA 9005-D94
DIN 51517 Part 3
MIL -L-2105B/C

Typical Characteristics

SAE Viscosity Grade	ISO 150
Viscosity @40C	150.cSt
Viscosity @ 100C	14.99cst
Kinematic Viscosity Index	100
Density @ 20C	0.8920
Pour Point	-21 deg.C
Flash Point	>212
Appear	Bright and Clear
Water Crackle	Negative