



PRODUCT DATA SHEET

KZN SUPER 15W-40 (CI-4/SL)

MULTIPURPOSE DIESEL AND GASOLINE ENGINE OIL

Description

KZN SUPER SAE 15W-40 is blended with refined high quality base oils including multifunctional additives which is suitable for universal performances over a long period.

Advantages

- High Temperature Stability
- Withstands very severe service conditions like four strokes and turbo charge.
- Reduce Oil consumption
- Longer drain intervals
- Reduce cylinder wear and keep pistons cleaner.

Applications

KZN SUPER SAE 15W/40 is recommended for turbo diesel and mixed fleet of both the diesel and petrol engines in severe loading services. Mixed fleets both old and new machines or equipment and stop start vehicles. In all types of generator sets and mobile hydraulic systems. The advanced detergent and load carrying additives used are capable of keeping engines super clean, protect stressed component, and control bore polishing.

Quality Levels

The SUPER SAE 15W-40 Multigrade Oil meets the following requirements:

API CI-4/ CH-4/ CG-4/CF-4/SJ/SL.

ACEA E7-04.

Jaso DH-1

MB 228.3

MAN M3275

Volvo VDS-3

Allison C4 Level .

Global DHD-1

Renault Truck RLD-2

Cummins CES 20076/77/78

MACK EO-M+

MTU Type 2.

Typical Characteristics

SAE Viscosity Grade	15W/40
Viscosity @ 40C	115.3cSt
Viscosity @ 100C	14.43cSt
Kinematic Viscosity Index	127
Density @ 20C	0.8840kg/l
Pour Point	-30deg.C
Flash Point	>200
Appearance	Bright and Clear